


37 157 000 FLUSH VALVE FOR WC



PRODUKTA APRAKSTS

- concealed installation
- $\frac{3}{4}$ "
- stop valve
- 6 - 14 l adjustable
- for low pressure
- for wash-down and wash-out bowls
- flow pressure range from 0.6 - 3.0 bar (min. static pressure 1.5 bar)
- with flow rate adjustment
- box for concealed installation with flush elbow
- flush pipe adjustable in length
- without wall plate/actuation



37 157 000 FLUSH VALVE FOR WC



REZERVES DAĻAS, jūlijs 2008 – tagad

- 1: Hand wheel (Rezerves daļas Nr. 43043000)
- 2: Cover (Rezerves daļas Nr. 43122000)
- 3: Piston (Rezerves daļas Nr. 43451000)
- 3.1: Sleeve (Rezerves daļas Nr. 4376900M)
- 4: Supply stop (Rezerves daļas Nr. 43405000)
- 5: Safety valve (Rezerves daļas Nr. 43422000)
- 5.1: Membrane (Rezerves daļas Nr. 4377300M)
- 6: Operating rod (Rezerves daļas Nr. 43067000)
- 7: Discharge sleeve (Rezerves daļas Nr. 43326000)
- 8: Throttle nozzle (Rezerves daļas Nr. 43408000)
- 9: Set of seals (Rezerves daļas Nr. 43012000)*

* Izvēles aksesuāri