

38 422 000 FLUSHING CISTERN FOR WC



PRODUKTA APRAKSTS

- 6 - 9 l adjustable
- concealed installation
- 0.82 m installation height
- dual flush discharge valve, pneumatic
- front or top actuation
- water supply from left/right or top
- low noise (group I acc. to German Noise Specification)
- insulated against condensation
- 415 x 410 x 360 mm
- 1/2" water supply connection
- fixing brackets
- flush pipe
- shortable inspection shaft incl. protection during construction phase
- without wall plate/actuation
- GROHE Water Saving - Less water, perfect flow
- for mounting of small flush plates please order revision shaft 40 950 000 (sold separately)

38 422 000 FLUSHING CISTERN FOR WC



REZERVES DAĻAS, jūlijs 2013 – tagad

- 1: Headpart (Rezerves daļas Nr. 42385000)
- 2: Overflow Sleeve (Rezerves daļas Nr. 43325000)
- 2.1: Sealing washer (Rezerves daļas Nr. 0319100M)
- 3: Support device (Rezerves daļas Nr. 42195000)
- 4: Filling valve (Rezerves daļas Nr. 37095000)
- 4.1: Lever (Rezerves daļas Nr. 43734000)
- 4.1.1: Seal (Rezerves daļas Nr. 4377000M)
- 4.2: Valve head (Rezerves daļas Nr. 43536000)
- 4.3: Membrane (Rezerves daļas Nr. 4375800M)
- 4.4: Screw cap (Rezerves daļas Nr. 43735000)
- 4.5: Valve float, 5 pcs. (Rezerves daļas Nr. 4379100M)
- 4.6: Set of seals (Rezerves daļas Nr. 43722000)*
- 5: Inspection shaft for flushing cistern (Rezerves daļas Nr. 42326000)
- 6: Discharge valve AV1 complete (Rezerves daļas Nr. 42314000)
- 6.1: Pneumatic hose (Rezerves daļas Nr. 42319000)
- 6.2: Seal (Rezerves daļas Nr. 42310000)
- 6.3: Valve seat for GD2 (Rezerves daļas Nr. 42315000)

* Izvēles aksesuāri