

38 786 001 **RAPID SL ELEMENT FOR URINAL WITH GROHE RAPIDO U**



PRODUKTA APRAKSTS

- 1.13 and 1.30 m installation height
- for manual actuation or Tectroninfra-red electronic 6 V or 230 V
- for on-the-wall installations or studded walls
- powder coated steel frame, self-supporting
- for dry-cladding, completely pre-assembled
- height adjustable fitting connections
- quick adjustment, lockable
- fixing material
- TÜV approved
- HT-outlet bend Ø 50 mm
- fixing bolts M8, with fixing device for ceramic
- inlet connection and inlet connecting set
- water group with stop valve
- flow pressure min 0.5 bar
- operating pressure max 10 bar
- flush aid
- functional unit checked ex factory
- water supply connections 1/2" outer thread
- connecting box for mains supply 230 V
- installation box with gasket
- shortable inspection shaft incl. protection during construction phase for sets for final installation with dimensions 116 x 144 mm
- for on-the-wall installation please order wall brackets 38 558 00M (sold separately)



38 786 001 **RAPID SL ELEMENT FOR URINAL WITH GROHE RAPIDO U**

REZERVES DAĻAS, marts 2011 – tagad

1: Outlet elbow 2" (Rezerves daļas Nr. 42943000)

1.1: Holder for outlet elbow (Rezerves daļas Nr. 42236000)

2: Threaded bolt (Rezerves daļas Nr. 43078000)

3: Fixation (Rezerves daļas Nr. 4307500M)

4: Transformer connecting box (Rezerves daļas Nr. 42279000)

5: Inspection shaft (Rezerves daļas Nr. 66838000)

6: Supply stop (Rezerves daļas Nr. 43392000)

7: Wall brackets (Rezerves daļas Nr. 3855800M)*

* Izvēles aksesuāri

