


39 140 000 **RAPID SL ELEMENT FOR WC, 1.13 M INSTALLATION HEIGHT WITH FIXING ELEMENT FOR BACK SUPPORT AND SUPPORT RAILS**




| A | 1080 | 1130 |
|---|------|------|
| B | 230 | 280 |
| C | 910 | 960 |
| D | 950 | 1000 |
| E | 1010 | 1060 |

PRODUKTA APRAKSTS

- with flushing cistern GD 2, 6 - 9 l
- for the disabled
- for WC bowls 70 cm projection
- for on-the-wall installations or studded walls
- powder coated steel frame, self-supporting
- for dry-cladding, completely pre-assembled
- with fixed connections
- quick adjustment, lockable
- fixing material
- TÜV approved
- 2 WC fixing bolts
- 4 wall brackets
- fixing device for ceramic
- distance of fixing bolts 180/230 mm
- PP outlet bend Ø 90 mm
- depth adjustable
- PP reducer Ø 90/110 mm
- inlet and outlet connecting set
- flushing cistern GD 2, 6 - 9 l, containing following features:
 - adjustment ex factory 6 l and 3 l
 - pneumatic discharge valve offering 3 modes of operation: dual flush or start/stop or single flush
- water supply from left/right or back
- low noise (group I acc. to German Noise Specification)
- insulated against condensation
- 1/2" water supply connection including integrated angle valve and push fit flexible hose union
- no tools required for the installation of the inspection shaft incl. protection during construction phase
- including wall brackets 38 558 00M for on-the-wall installation
- for mounting of small flush plates please order revision shaft 40 911 000 (sold separately)

39 140 000 **RAPID SL ELEMENT FOR WC, 1.13 M INSTALLATION HEIGHT WITH FIXING ELEMENT FOR BACK SUPPORT AND SUPPORT RAILS**



REZERVES DAĻAS, jūnijs 2014 – tagad

- 1: Threaded bolt (Rezerves daļas Nr. 4276400M)
- 2: WC inlet and outlet connecting set (Rezerves daļas Nr. 37311K00)
- 2.1: Basin fastening (Rezerves daļas Nr. 43511SH0)
- 2.2: Connector (Rezerves daļas Nr. 37119000)
- 3: PP-outlet bend Ø 90 mm (Rezerves daļas Nr. 42327000)
- 4: Reducer (Rezerves daļas Nr. 42242000)
- 5: Support for outlet bend (Rezerves daļas Nr. 42243000)
- 6: Inspection shaft (Rezerves daļas Nr. 66791000)
- 7: Filling valve (Rezerves daļas Nr. 37095000)
- 7.1: Lever (Rezerves daļas Nr. 43734000)
- 7.1.1: Seal (Rezerves daļas Nr. 4377000M)
- 7.2: Valve head (Rezerves daļas Nr. 43536000)
- 7.3: Membrane (Rezerves daļas Nr. 4375800M)
- 7.4: Screw cap (Rezerves daļas Nr. 43735000)
- 7.5: Valve float, 5 pcs. (Rezerves daļas Nr. 4379100M)
- 7.6: Set of seals (Rezerves daļas Nr. 43722000)*
- 8: Support device (Rezerves daļas Nr. 42246000)
- 9: Tube (Rezerves daļas Nr. 42233000)
- 9.1: Sealing washer (Rezerves daļas Nr. 0319100M)
- 10: Headpart (Rezerves daļas Nr. 42385000)
- 11: Dual Flush discharge valve AV1 (Rezerves daļas Nr. 42320000)
- 11.1: Extension for overflow pipe (Rezerves daļas Nr. 42313000)
- 11.2: Pneumatic hose (Rezerves daļas Nr. 42319000)
- 11.3: Seal (Rezerves daļas Nr. 42310000)
- 12: Valve seat for GD2 (Rezerves daļas Nr. 42315000)
- 13: Wall brackets (Rezerves daļas Nr. 3855800M)
- 14: Set for noise protection (Rezerves daļas Nr. 37131000)*
- 15: Retro-fit set (Rezerves daļas Nr. 38796000)*
- 16: 4.5 l adapter for GD2 (Rezerves daļas Nr. 42333000)*
- 17: Radio electronic (Rezerves daļas Nr. 39141000)*
- 18: Radio electronic (Rezerves daļas Nr. 38759SD0)*
- 19: Radar 868.4 MHz (Rezerves daļas Nr. 38758000)*
- 20: Radio transmitter (Rezerves daļas Nr. 39142000)*
- 21: WC control for manual remote actuation (Rezerves daļas Nr. 38934SD0)*
- 22: Flush plate (Rezerves daļas Nr. 38564000)*
- 23: Pneumatic actuation (Rezerves daļas Nr. 37059000)*

* Izvēles aksesuāri